



KEEP EMPOWERING
YOURSELF SUCCESSFULLY

TEST REPORT

BS EN 62479-2010

Product : Led Bracelet
Model Name : GFB001
Brand : GFLAI-001
Report No. : KEYS21091509002EM-02

Prepared for

Shenzhen Greatfavonian Electronic CO.,LTD.

5F,Tongfuyu Industrial Park,Lezhujiao ,Zhoushi Road, Baoan District, Shenzhen,China 518126

Prepared by

Dongguan KEYS Testing Technology Co., Ltd.

6 / f, Building B, Chuangyigu Industrial Park, No.5 Hehe Street, Songxi Road, Hengkeng, Liaobu,
Dongguan City

1 TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Greatfavonian Electronic CO.,LTD.
Address : 5F,Tongfuyu Industrial Park,Lezhujiao ,Zhoushi Road, Baoan District, Shenzhen,China 518126
Manufacture's name : Shenzhen Greatfavonian Electronic CO.,LTD.
Address : 5F,Tongfuyu Industrial Park,Lezhujiao ,Zhoushi Road, Baoan District, Shenzhen,China 518126
Product name : Led Bracelet
Model name : GFB001

This device described above has been tested by KEYS, and the test results show that the equipment under test (EUT) is in compliance with the Radio Equipment Regulations 2017 requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of KEYS, this document may be altered or revised by KEYS, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests: September 15, 2021 to September 24, 2021

Date of Issue: September 26, 2021

Test Result: **Pass**

Test Engineer:

Technical Manager:

Sunny Li/ Engineer


Jason Zhan / Manager

Contents

Page

1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE EVALUATION	6
4.1 LIMITS.....	6
4.2 TEST RESULT OF RF EXPOSURE EVALUATION.....	6

2 Test Summary

Test	Test Requirement	Test Method	Limit / Severity	Result
RF Exposure	BS EN 62479	BS EN 62479	-	PASS

Remark:

N/A: Not Applicable

RF: In this whole report RF means Radio Frequency.

A.M. Amplitude Modulation.

P.M. Pulse Modulation.

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Led Bracelet
Model Name	:	GFB001
Bluetooth Version	:	/
Operating frequency	:	433MHz
Numbers of Channel	:	5
Antenna Type	:	Internal PCB Antenna
Antenna Gain	:	2.5dBi
Type of Modulation	:	ASK
Power supply	:	6V(2*3V Button batteries), 18mA, 108mW
Hardware Version	:	A1
Software Version	:	A1

Note:

For more details, please refer to the User's manual of the EUT.

BT-CM means Bluetooth BR/EDR

BT-LE means Bluetooth Low Energy

4 RF Exposure Evaluation

4.1 Limits

According to Council Recommendation: the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

Reference levels for electric, magnetic and electromagnetic fields (10MHz to 300GHz)

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level P_{max} .

Annex A contains example values for P_{max} derived from existing exposure limits listed in the bibliography, such as the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2], and IEEE Std C95.1-2005 [3].

For wireless devices operated close to a person's body with available antenna powers and/or average total radiated powers higher than the P_{max} values given in Annex A, the alternative P_{max} values (called P_{max}'), described in Annex B can also be used.

For low power equipment using pulsed signals, other limits may apply in addition to those considered in Annex A and Annex B. Both ICNIRP guidelines [1] and IEEE standards [2], [3] have specific restrictions on exposures to pulsed fields, and the requirements of those standards with respect to exposure to pulses shall be met. Annex C discusses this topic further.

4.2 Test Result of RF Exposure Evaluation

Test Mode	Transmit
Limit (P_{max})	20mW/13dBm

After performed the test at low/middle/high channel, the below recorded is the worst.

Max. Peak Output Power (dBm)	P_{max} (dBm)
0.48	13

Remark: Since the max. peak output power is less than the applicable low-power exclusion level P_{max} , this device is deemed to comply with the provisions of this standard without further testing.

*****THE END REPORT*****